



DOBAU[®] - S

bitumen-solvent based protective coat without fillers

Uses:

Finish coat for roof sheets and other bitumen containing roof coverings. DOBAU[®] - S has also got a sealing effect against ground moisture on floor coverings as well as on walls of ground reaching building parts.

Properties:

DOBAU[®] - S distinguishes itself by the following characteristics:

- it fulfils the requirements of AIB DS 835
- it is thinned ready to use
- very good bonding to bitumen and mineral subsoil
- can also be applied on moist subsoil
- is resistant against aqueous solvents, diluted acids, salts, lime, cement or similar
- fast drying
- dust binding

Application instructions:

Weather conditions:

At the application of DOBAU[®] - S the air and surface temperatures have to be at least 5°C. Effects by water, rain or frost have to be avoided during the application and drying out time.

Subsoil and application:

The subsoil where DOBAU[®] - S shall be applied, have to be dry and free from oils, greases and loose particles. Before the application DOBAU[®] -S has to be completely homogenized by mixing. DOBAU[®] - S can be applied by brush or gun.

Theoretical material consumption:

For 1 mm dry layer thickness you need approx. 1,4 kg/m² of DOBAU[®] - S.
And approx. 0,4-0,5 kg/m² for each coat.

Storage:

Storable in unopened original packages for at least 12 months. The packages have to be stored free from frost and must not be exposed to direct sunshine or excessive warming actions. The prescription for inflammable liquids is valid (VfB).

Form of supply:

5 l, 10 l and 30 l tins

Cleaning agent:

in set state: commercial solvents or petrol; at skin contact hand washing paste

Technical data:

Type of binder:	bitumen
Kind of solvent:	white spirit
Nature:	liquid
Flashing point (DIN 53 213):	approx. 30°C
Density (DIN 52 004):	approx. 0,84 g/cm ³
Emergency hint:	R10 inflammable

This product information is in accordance with our current information; the stated data are average values under normal conditions. The applicator is obliged to check the suitability and the possible applications for the intended purposes. For special technical information please do not hesitate to contact us. Our products are sold subject to our General Terms and Conditions of Sale.

Dortmunder Gußasphalt GmbH & Co. KG, Am Hafenbahnhof 10, D-44147 Dortmund,

Telefon: +49 (0)231/395797-0, Fax: +49 (0)231/395797-71, Internet: www.dga.de, E-mail: info@dga.de Stand: 08/16